

[54] **HANDWRITTEN KEYBOARDLESS ENTRY COMPUTER SYSTEM**

[75] Inventor: **Ralph Sklarew**, Reston, Va.

[73] Assignee: **Grid Systems Corporation**, Fremont, Calif.

[21] Appl. No.: 29,772

[22] Filed: **Mar. 24, 1987**

Related U.S. Application Data

[63] Continuation-in-part of Ser. No. 889,513, Jul. 25, 1986, abandoned.

[51] Int. Cl.⁵ **G06K 9/22**

[52] U.S. Cl. **382/13; 382/57; 382/59; 178/18**

[58] Field of Search **382/13, 24, 57, 14; 340/706, 707, 709; 178/18, 19, 20**

[56] **References Cited**

U.S. PATENT DOCUMENTS

3,699,439	10/1972	Turner .	
3,832,693	8/1974	Ishizaki et al.	340/707
3,903,517	9/1975	Hafner	382/57
4,112,415	9/1978	Hilbrink	382/13
4,177,354	12/1979	Mathews	178/18
4,177,448	12/1979	Brayton	382/14
4,184,147	1/1980	Seelbach	382/13
4,365,235	12/1982	Greanias et al.	382/13
4,456,787	6/1984	Schlosser et al.	178/19
4,475,239	10/1984	van Raamsdonk	382/57
4,578,811	3/1986	Inagaki	382/13
4,641,354	2/1987	Fukunaga et al.	382/13

4,672,677	6/1987	Yamakawa	382/13
4,679,241	7/1987	Lukis	178/19
4,680,430	7/1987	Yoshikawa et al.	178/19
4,680,804	7/1987	Kusunuki et al.	382/13

FOREIGN PATENT DOCUMENTS

55-143681	10/1980	Japan	382/13
2117154	10/1983	United Kingdom	382/13

Primary Examiner—Leo H. Boudreau

Attorney, Agent, or Firm—Townsend & Townsend

[57] **ABSTRACT**

A keyboardless entry computer system includes a transparent input screen that generates positional information when contacted by a stylus, and a display screen mounted physically below the input screen such that a character that is displayed can be seen below the input screen. The system includes a computer that has been programmed to compile the positional information into Strokes, to calculate Stroke characteristics, and then compare the Stroke characteristics with those stored in a database in order to recognize the symbol drawn by the stylus. Key features of the system are: (1) transparent position sensing subsystem; (2) underlying display on which to mimic drawing of sensed positions and to show characters or symbols; (3) means to convert sensed positions first into plotted Points and then into recognized characters or symbols; and (4) means to "learn" to associate sensed input positions with a character or symbol.

21 Claims, 14 Drawing Sheets

